

Class 1

Burlington Baths

Product Disclosure Information Self-Assessment

Version: V110823

Product name	Burlington Baths
Product line	Freestanding and Clawfoot baths from the Burlington range
Product identifier	Windsor, London, Admiral, Harewood, Emperor

Product description

Burlington baths are made from twin skinned fused and re-enforced acrylic. They have a white glossy finish.

The bath dimensions are: 1500-1800mm L 635-770mm H 705-850mm W

Relevant building code clauses

B2 Durability — B2.3.1 (c)

F2 Hazardous building materials — F2.3.1

G1 Personal Hygiene — G1.3.2

G12 Water Supplies — G12.3.5

Contributions to compliance

- B2 Durability B2.3.1 Burlington Baths carry a 5 year domestic or 1 year non-domestic warranty. Extended guarantees on Burlington products are available from the manufacturer, Bathroom Brands Group. For more information and terms and conditions, visit www.burlingtonbathrooms.com/guarantee
- F2 Hazardous building materials o F2.3.1 Burlington Baths are safe when handled. There are no requirements for this product in order to comply with Acceptable Solution F2/AS1, First Edition Amendment 3, 2017.
- G1 Personal Hygiene o G1.3.2 Burlington Baths shall be installed to: facilitate sanitation, avoid harbouring dirt or germs, allow effective cleaning, discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and provide a healthy safe disposal system when non-water-borne disposal is used Sanitary fittings should be easy to locate and identify, with their operation easy to understand and suitable for both standing and seated users.

First party self-assessment generated Oct 4, 2023 with BPIR Ready.

Source: <https://bpir.nz/form/view?wz=ceee09f641fa14962cff35674113879c86b27aa9>

Get BPIR Ready | bpir.nz

•G12 For Water supplies G12, the prime building product objective is to ensure that the product used in water supply will not contaminate potable water either by way of material leaching into the water or cross connections and will not leak.

Scope of use

Burlington baths are intended for domestic and commercial use. They are designed to enclose water. They can be used with water temperatures up to 55 degrees celsius.

Burlington baths are to be installed using the recommended Burlington waste fitting, or those supplied with bath.

These baths are to be mounted on a rigid floor surface.

Conditions of use

Burlington baths must be installed in accordance with the instructions provided. We recommend these baths are installed by an authorised installer. Floor surfaces must be flat and free of movement.

This product is intended for domestic and commercial use. This product is cleanable and impervious to moisture — cleaning of the bath shall be done in accordance with the manufacturer's cleaning instructions.

Supporting documentation

The following additional documentation supports the above statements:

Title (type)	Version	URL
Burlington Bath Information (Design, Installation)	V110823	https://www.bathco.co.nz/bathrooms/baths
Burlington Bath Warranty (Warranty)	V110823	https://www.bathco.co.nz/warranties
Bathroom Brands Warranty (Warranty)	V110823	https://bathroombrands.com/guarantee#/first-step

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Bathroom Brands Group
Legal and trading name of importer	Bath Co.
Importer address for service	86 Wigram Road Christchurch 8025
Importer website	www.bathco.co.nz

Importer NZBN	9429041650790
Importer email	info@bathco.co.nz
Importer phone number	033430969

Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

Appendix

BPIR Ready selections

Category: Sanitary fixtures and appliances [legacy category]

	Yes	No
Suitable for Accessible facilities		x
Provision of hot water	x	

Building code performance clauses

All relevant building code performance clauses listed in this document:

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

- (c) 5 years if:
- i. the *building elements* (including services, linings, renewable protective coatings, and *fixtures*) are easy to access and replace, and
 - ii. failure of those building elements to comply with the *building code* would be easily detected during normal use of the *building*.

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G1 Personal Hygiene

G1.3.2

Sanitary fixtures shall be located, constructed and installed to:

- a. facilitate *sanitation*,
- b. avoid risk of food contamination,
- c. avoid harbouring dirt or germs,
- d. provide appropriate privacy,
- e. avoid affecting occupants of adjacent spaces from the presence of unpleasant odours, accumulation of offensive matter, or other source of annoyance,
- f. allow effective cleaning,
- g. discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and
- h. provide a healthy safe disposal system when non-water-borne disposal is used.

G12 Water Supplies

G12.3.5

Sanitary fixtures and *sanitary appliances* must be provided with hot water when intended to be used for

- a. utensil washing; and
- b. personal washing, showering, or bathing.